




**Ramset**<sup>®</sup>  
*DRIVING JOBSITE SPEED*



# Notes



## TABLE OF CONTENTS



Tools At A Glance.....	R 4
Introduction to Gas Technology.....	R 6
T4MAG.....	R 8
T4SS Conversion Kit.....	R 10
TrakFast - TF1200.....	R 12
T4 I-F Compact.....	R 16
Introduction to Powder Fastening Systems.....	R 21
Training and Certification.....	R 22
RA27.....	R 23
Cobra+.....	R 24
Cobra+ Insulfast.....	R 25
Hammer Shot 22 cal.....	R 26
Mastershot 22 cal.....	R 26
TriggerShot 22 cal.....	R 26
Troubleshooting.....	R 27
Problem Solving Pins.....	R 30
Powder Fasteners.....	R 31
Powder Loads.....	R 33
Suggested Specifications.....	R 34
Performance Data/Submittal Information.....	R 35
TE Performance Data/Submittal Information.....	R 37

TOOL	DESCRIPTION	TYPICAL BUILDING TRADE
 <p>(see page R 8)</p>	<p><b>T4MAG</b> 45-Pin Magazine Cross Over Technology 2 Year Warranty</p> <p>Length: 17" Height: 16-1/4" Weight: 8.55 lbs. Maximum Pin Length: 1"</p>	<p><b>WALLS &amp; CEILINGS</b></p>
 <p>(see page R 12)</p>	<p><b>TF1200</b> Fully Automatic 42-Pin Magazine 1-1/2" Pin Capacity 2 Year Warranty</p> <p>Length: 17" Height: 15-1/2" Weight: 8.375 lbs. Maximum Pin Length: 1-1/2"</p>	<p><b>WATERPROOFING WALLS &amp; CEILINGS</b></p>
 <p>(see page R 16)</p>	<p><b>T4 I-F COMPACT</b> Fully Automatic Single Pin Gas Tool Fuel Injection 2 Year Warranty</p> <p>Length: 20.25" Height: 12.4" Weight: 7.3 lbs. Maximum Pin Length: 8"</p>	<p><b>INSTALLATION FOR WALLS &amp; CEILINGS FOUNDATION &amp; WATER PROOFING</b></p>

	TOOL	DESCRIPTION	TYPICAL BUILDING TRADE
.27 CAL STRIP TOOL	 <p><b>RA27</b> Fully Automatic Low Velocity Piston Type Fastening Tool 3 Year Warranty</p> <p>(see page R 23)</p>	<p><b>Part No. RA27</b> Length: 15" Weight: 5.3 lbs. Muzzle Bushing O.D.: 9/16" Maximum Pin Length: 1-1/2" (2" w/washer)</p>	<p><b>WALLS &amp; CEILINGS</b></p>
	 <p><b>COBRA+</b> Semi-Automatic Economical 1 Year Warranty</p> <p>(see page R 24)</p>	<p><b>Part No. COBRA+</b> Length: 15" Weight: 5.25 lbs. Muzzle Bushing O.D.: 9/16" Maximum Pin Length: 2-1/2" (3" w/Washer)</p>	<p><b>WALLS &amp; CEILINGS</b></p>
	 <p><b>COBRA+ INSULFAST</b> Accessory for Converting Cobra+ into Insulation Fastening Tool</p> <p>(see page R 25)</p>	<p><b>Part No. COBRAIFKIT</b> Length: 19" Weight: 5.25 lbs. Insulation thickness range: 1" - 2" *Other sizes available on special request</p>	<p><b>INSTALLATION FOR WALLS &amp; CEILINGS  FOUNDATION &amp; WATER PROOFING</b></p>

.22 CAL SINGLE SHOT TOOLS	<p><b>HammerShot</b></p>  <p><b>Part No. 45000</b> Application: Basement renovations Maximum Pin Length: 2-1/2" .22 caliber single shot loads: 2, 3, 4</p> <p>(see page R 26)</p>	<p><b>MasterShot</b></p>  <p><b>Part No. 45100</b> Application: Basement renovations applications in concrete and steel Maximum Pin Length: 2-1/2" (3" w/washer) .22 caliber single shot loads: 2, 3, 4</p> <p>(see page R 26)</p>	<p><b>TriggerShot</b></p>  <p><b>Part No. 45200</b> Application: Basement renovations Maximum Pin Length: 2-1/2" .22 caliber single shot loads: 2, 3, 4</p> <p>(see page R 26)</p>
---------------------------	--	---	---

## Intro to Gas Technology

ITW saw a challenge: how to create a portable tool that delivered the power of pneumatic tools without the hoses and compressors. In 1991, ITW Paslode conquered the challenge with the revolution of gas-powered technology. The cordless Impulse Finish Nailer delivered the power of pneumatic tools without cluttering job sites.

With the thought of Driving Jobsite Speed while creating a safer work environment, ITW Ramset built upon the Paslode technology and in 1992 introduced the TrakFast to the drywall trade. It forever changed the way the world worked. In 2003, ITW Ramset followed up on the success of the TrakFast with the T3SS which is setting the standard for electrical and mechanical contractors.



Drywall



Electrical



Mechanical


- No Licensing Required
- Fast and Easy to Use
- Quiet—No Recoil
- No Cords or Hoses
- Long Fuel Cell & Battery Life


Gas significantly lowers cost-in-place, reduces stress on the employee, and it's much quieter to use than drilling or powder actuated tools (PATs), so you can work in occupied buildings. There are times when you need the power and accuracy of our PATs—like the speed of our fully automatic RA27 tool, or the work horse, nearly maintenance-free Cobra+ semi-automatic PAT. But constant use of these tools can be noisy and overly jarring on the body.

### When the conditions are right, gas is the right choice.

**Problem:**  
*"My guys work on block all day long—from electrical boxes to furring. I've tried powder tools and they blow holes in block. What makes the Ramset technology different?"*

**Solution:**  
Ramset technology has patented overdrive technology built in to every gas-powered tool. The tool works under the same principal as a combustion engine. A little gas, a little spark and a powerful shot, without the recoil associated with powder.





**GAS      POWDER**

# The industry transitions to gas technology




**Problem:**

*"I don't want to have to re-license my guys to work with gas technology"*

**Solution:**

*Since there are no loads, there's no licensing needed. In fact, Union Trainers have begun including the Ramset Gas Tools in training classes, and students can't believe how easy the tools are to work with.*

*In addition, the gas powered tools are totally portable and can be used for almost all your jobs—without the worry of having unspent loads on your jobsite.*




## The Inside Story

The patented Ramset technology delivers precisely balanced power eliminating the damage caused by overdrive in PATs.

How it works: As the nosepiece is depressed, a rechargeable battery turns on the fan motor. In less than a second: a precise amount of fuel is injected into the combustion chamber. When the trigger is pulled, a spark creates an explosion that drives the piston into the fastener, and the fastener in the work surface. The action creates a vacuum that pulls the piston back to the start position.

In fact the technology is so precise it won't blow through a pop can.



# T4MAG

## Gas Powered Tool

**Gas Technology**  
**45 Pin Magazine**  
**Best balanced**  
**tool available**



### DESCRIPTION/SUGGESTED SPECIFICATIONS

#### Automatic Fastening System—

#### THE OPERATOR'S CHOICE—THE PREMIER FASTENING SYSTEM FOR THE COMMERCIAL DRYWALL CONTRACTOR


Ramset's T4MAG is the best-balanced tool available and is easy to use overhead. With 30% more power to work in the toughest concrete, this tool will drive your job site productivity and result in lower user fatigue and downtime.

### ADVANTAGES


- Higher stick rate than industry standard
- 30% more power to work in the toughest concrete
- Drives pins flush to create full embedment
- Lower pushdown force and shorter travel distance decrease user fatigue
- Reduced jamming, resulting in less downtime on the job
- Superb balance leads to optimal user experience

#### T4MAG Increase Your Range with Overhead Power

The Power of the T4MAG allows you to consistently shoot where no other gas tool has gone before. The .125 diameter pin is specifically engineered to work in the toughest concrete and steel where other pins cannot perform. The new T4MAG system delivers power that rivals other gas and powder systems.



Setting aggregate is the biggest reason for overhead pin failure.



With the T4's 1/2" steel pin you can even shoot into the web of steel.

### SPECIFICATIONS

Part number: T4MAG

Length: 17"

Height: 16-1/4"

Weight: 8.55 pounds

Battery capacity: 10,000 shots

Magazine capacity: 45 pins

Maximum pin length: 1"

Operating temperatures: -15°C - 48°C

### MOST COMMON FASTENERS

#### T4MAG Fuel/Pin Pack

1000 PINS AN 2 FUEL CELLS PER INNER PACK


PART NUMBER	SHANK LENGTH IN. (mm)	DESCRIPTION (Comes with T4 Fuel)
T4012SM	1/2 (12.7)	T4 1/2" Plated premium steel pin
T4034SM*	3/4 (19.1)	T4 3/4" Plated step shank concrete pin
T4100**	1 (25.4)	T4 1" Plated concrete pin

• Collated on the point instead of on the head to significantly reduce pin jams

Shank diameter = .125 \*Shank diameter = .104 / .125 Head diameter = .250

\*\* \*\* 510 pins and 1 fuel cell per inner pack


## APPLICATIONS



Track to Steel



Track to Concrete



Deep Leg Track

## APPROVALS/LISTING

ICC ESR 1955 - Fasteners

COLA RR-22668 - Fasteners

## TOOL ACCESSORIES



Part No. T4FUEL  
Fuel Cell - T4  
Qty: 12 (4-3packs)



Part No. 019903  
Battery - T4MAG  
Qty: 1



Part No. 018866  
Battery Charger - T4MAG  
Qty: 1



# T4SS Conversion Kit



## T4SS - Conversion Kit Convert your T4MAG

### ADVANTAGES

- Tapered Design: The tool is engineered to reach into tight areas
- Adjustable depth of drive for optimal performance
- Auto shut-off/on avoids drain on lithium-ion battery
- Smaller 510-shot fuel cell to keep better track of the day's progress
- Fuel and battery gauges eliminate interruptions
- Scaffold hook keeps your tool within reach



Higher stick rate than industry standard



Easy push-down force decreases user fatigue



30% more power to work in hard concrete



Preassembled fasteners for optimal job performance and easy ordering



Drives pins flush to create full embedment



Superb balance leads to optimal user experience

### SELECTION CHART

#### One Hole Strap


Used to attach conduit or armored cable to concrete. Fastener pre-assembled to a 16 gage conduit strap. 100 per jar, 3/8" 200 per jar and 1-1/4" 25 per jar.



PART NUMBER	SHANK DIAMETER	HEAD DIAMETER	DESCRIPTION
38HSMP034	.104/.125	.300	3/8" Hole strap with 3/4" plated pin
12HSMP034	.104/.125	.300	1/2" Hole strap with 3/4" plated pin

#### Tie Strap Holder

Used to install temporary lighting and secure low voltage cable to concrete, uses a standard cable tie up to 3/8" in width. Fastener pre-assembled to an 22 gage tie strap holder. 50 per jar.



PART NUMBER	SHANK DIAMETER	HEAD DIAMETER	DESCRIPTION
TSHMP034	.104/.125	.300	Tie strap holder with 3/4" plated pin

## PIN SPECIFICATIONS

Made from AISI 1060-1065 steel Austempered to a core hardness of 52-56 Rc

Typical tensile strength: 270,000 psi

Typical shear strength: 162,000 psi

Standard finish

- Proprietary black
- Mechanical zinc plate to a minimum thickness of .0002 meets requirements of ASTM 8695
- Electroplated zinc with yellow chromate

## APPROVALS/LISTING

ICC Evaluation Service, Inc.

#ESR 1955 T3 Fasteners

## APPLICATIONS

Mechanical Trades

Electrical Trades

Plumbing Trades

## Fasteners in Concrete


FASTENER PART NUMBER	SHANK DIA. (INCH)	MINIMUM PENETRATION (INCH)	INSTALLED IN STONE AGGREGATE CONCRETE CONCRETE COMPRESSIVE STRENGTH ALLOWABLE LOAD – <i>Ultimate Load</i>						HOLLOW BLOCK Grade N, Type 1	
			4000 PSI		6000 PSI		3000 PSI Lightweight LOWER FLUTE		FACE SHELL Min 1-1/4" face thickness	
			TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)
MP034TH*	0.125	5/8	<b>78</b> 426	<b>80</b> 574	<b>62</b> 308	---- ----	<b>72</b> 361	<b>242</b> 1210	<b>133</b> 691	---- ----
		3/4	<b>104</b> 593	<b>195</b> 977	<b>132</b> 658	<b>206</b> 1057	<b>93</b> 470	<b>288</b> 1442	<b>84</b> 444	<b>87</b> 446
38HSMP034, 12HSMP034 TSHMP034	0.104/ .125	5/8	<b>60</b> 357	<b>117</b> 587	<b>107</b> 533	<b>191</b> 957	<b>54</b> 269	<b>230</b> 1150	<b>71</b> 357	<b>123</b> 613

\*MP034TH is no longer available

# TrakFast

## TF1200 Gas Powered Tool

Fully Automatic  
1-1/2" Pin Capacity  
42 Pin Magazine  
Capacity



## DESCRIPTION/SUGGESTED SPECIFICATIONS

### Automatic Fastening System—

Since its introduction in 1991, TrakFast has been the tool of choice for both interior and exterior contractors. The TrakFast Automatic Fastening System fastens all types of track, from standard track to hat channel, deep leg, Z, and J channel. Contractors continue to report tremendous savings when using TrakFast for high production fastening. They have learned that TrakFast's actual cost in place beats all other systems. The



#### Fastening System Productivity

In the time it takes  
you to drive two pins  
with a powder tool,  
you can drive up to  
10 pins with TrakFast!

increased speed and productivity of TrakFast allows the contractor to bid more competitively, complete the job sooner and move on to the next job. Anyone can use TrakFast—just load the pins and fire. It's that easy!

## ADVANTAGES

- **SPEED** Three to five times faster than powder tools. 42-pin magazine reduces loading time.
- **EASY TO USE** Tool automatically resets piston. No recoil, tool absorbs shock resulting in less operator fatigue.
- **NO LICENSING REQUIRED** Unlike powder-actuated tools, no licensing is needed.
- **NO CHANGING LOADS** TrakFast uses a fuel cell, not a load. No need to inventory different colored loads.
- **NARROW NOSE AND PROFILE** Allows tool to reach inside deep leg track (1-5/8" wide x 2" high).
- **2 Year Warranty** (6 months on wearable parts).

### TrakFast's power comes from the battery and fuel cell

The 6-volt rechargeable Ni-CD battery can drive approximately 3000 shots per charge. The clean burning fuel cell can drive over 1000 pins and keeps the tool cleaner than powder actuated tools.



## MOST COMMON FASTENERS

PIN #	PIN LENGTH		MOST COMMON APPLICATION
	IN.	MM	
FPPSP916	9/16	14.3	Track to steel
FPP034B	3/4	19.1	Track to concrete
FPP114	1-1/4	31.8	Membering to concrete

See page R 14 for all fasteners.

## APPLICATIONS



Waterproofing to concrete



Track to concrete



Track to steel

## SPECIFICATIONS

**Part No. TF1200**

Length: 17"

Height: 15-1/2"

Weight: 8.375 lbs.

Maximum Capacity: 42 pins

Maximum cycles/second: 2


Fuel cell: 1000 shots

Battery (charged): 3000 shots

## APPROVALS/LISTING

ICC ESR-2579 - TrakFast Fasteners (Note: This report replaces ER-5001)

COLA RR-25264 - TrakFast Fasteners (City of LA)



*TrakFast ICC (ICBO) ER-5001 is the only approval that allows you to fasten into any location on a hollow block wall and won't blow away block like a powder tool.*

## TOOL ACCESSORIES




**Part No. 4821**  
Fuel Cell—TrakFast



**Part No. B0092**  
Battery—T3SS  
Qty: 1



**Part No. 100041LA**  
Disc Holding Probe  
(for TF1200 Telescoping Nose)  
Qty: 1



**SLIP-OVER CUP**  
**Part No. 7405161**  
For Cosella Dorken  
(DELTA-MS) Plugs  
Qty: 1



**Part No. LD100**  
Plated 1" Lathing Disc 22g  
Qty: 1,000 per box

**Part No. 219503**  
T3 Double Battery  
Charger  
Qty: 1

**Part No. 906014**  
T3 Single Battery  
Charger  
Qty: 1

## TRAKFAST GAS TOOL FASTENERS

*Ramset collated Gas Tool Fasteners are specifically engineered for optimal performance in Ramset Gas Power Tools using fastener magazines*

### SELECTION CHART

#### TrakFast Standard Fuel /Pin Pack

##### STRAIGHT SHANK



For high volume, repetitive fastenings to concrete and steel such as drywall track to concrete. 1,000 pins and 1 fuel cell per box.

PART NUMBER	SHANK LENGTH IN. (mm)	DESCRIPTION
FPP034B	3/4 (19.1)	3/4" Black pin
FPP114	1-1/4 (31.8)	1-1/4" Plated pin

Shank diameter = .109 Head diameter = .250

#### TrakFast Premium Fuel /Pin Pack

##### STEP SHANK



For high volume, repetitive fastenings to hard concrete and hard steel such as drywall track to hard concrete and steel. 1,000 pins and 1 fuel cell per box.

PART NUMBER	SHANK LENGTH IN. (mm)	DESCRIPTION
FPPSP916	9/16 (14.3)	9/16" Gold pin

Shank diameter = .104 / .118 Head diameter = .250

#### Trakfast Breakaway Strip Fuel/Pin

##### STRAIGHT SHANK



For high volume, repetitive fastenings to concrete such as wood furring to concrete. 1,000 pins and 1 fuel cell per box.

PART NUMBER	SHANK LENGTH IN. (mm)	DESCRIPTION
FPP112T	1-1/2 (38.1)	1-1/2" Plated pin

Shank diameter = .109 Head diameter = .250

**Ramset fasteners may be specified by their type or catalog number to satisfy fastening requirements.**

**PIN SPECIFICATIONS**

Made from AISI 1060-1065 steel. Austempered to a core hardness of 52-56 Rc  
 Typical tensile strength: 270,000 psi  
 Typical shear strength: 162,000 psi  
 Standard finishes  
 - Proprietary black  
 - Mechanical zinc plate to a minimum thickness of .0002 meets requirements of ASTM B695  
 - Electroplated zinc with yellow chromate

**APPROVALS/LISTING**

ICC Evaluation Service, Inc.

#ESR-2579 TrakFast Pins

City of Los Angeles

#RR-25264 TrakFast pins

**PERFORMANCE TABLES**
**Collated Gas Fasteners in Concrete**

PART NUMBER SERIES	SHANK DIAMETER (INCH)	MINIMUM PENETRATION (INCH)	INSTALLED IN STONE AGGREGATE CONCRETE – CONCRETE COMPRESSIVE STRENGTH							
			ALLOWABLE LOAD – <i>Ultimate Load</i>							
			2000 PSI		3000 PSI		4000 PSI			
		TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	
FPP - Straight Shank	0.109	5/8	<b>60</b> <i>434</i>	<b>55</b> <i>546</i>	<b>55</b> <i>453</i>	<b>75</b> <i>615</i>	<b>55</b> <i>472</i>	<b>95</b> <i>685</i>		
		3/4	<b>60</b> <i>595</i>	<b>80</b> <i>650</i>	<b>55</b> <i>583</i>	<b>95</b> <i>699</i>	<b>55</b> <i>571</i>	<b>115</b> <i>749</i>		
FPPSP - Step Shank	0.104/0.118	3/4	-----	-----	-----	-----	-----	<b>51</b> <i>256</i>	<b>83</b> <i>418</i>	

PART NUMBER SERIES	SHANK DIAMETER (INCH)	MINIMUM PENETRATION (INCH)	INSTALLED IN STONE AGGREGATE CONCRETE – CONCRETE COMPRESSIVE STRENGTH							
			ALLOWABLE LOAD – <i>Ultimate Load</i>							
			3000 PSI LIGHT WEIGHT CONCRETE		3000 PSI LIGHT WEIGHT CONCRETE WITH METAL DECK		HOLLOW CONCRETE MASONRY UNITS (CMU) ANY LOCATION			
		TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	
FPP - Straight Shank	0.109	5/8	<b>35</b> <i>234</i>	<b>55</b> <i>403</i>	<b>30</b> <i>239</i>	<b>205</b> <i>1025</i>	<b>35</b> <i>347</i>	<b>50</b> <i>435</i>		
		3/4	<b>80</b> <i>630</i>	<b>115</b> <i>756</i>	<b>40</b> <i>330</i>	<b>235</b> <i>1284</i>	-----	-----	-----	
FPPSP - Step Shank	0.104/0.118	3/4	-----	-----	-----	-----	<b>36</b> <i>184</i>	<b>58</b> <i>290</i>		

**Note 1:** ALLOWABLE loads are shown in the **LARGE BOLD** font, *Ultimate* loads are shown in *smaller italic* font. **Note 2:** Testing conducted in accordance with ICC AC70 & ASTM E1190. **Note 3:** Safety factors are based on coefficient of variation. In accordance with ICC AC70, the safety factor will be no less than 5. **Note 4:** Values shown in concrete are for the fastener only. Connected members must be investigated separately. **Note 5:** Cyclic, fatigue, shock loads, and other design criteria may require a different safety factor. **Note 6:** Job site testing may be required to determine actual job site values. **Note 7:** Minimum edge distance in concrete is 3 inches unless otherwise approved. **Note 8:** For SI: 1 lbf = 4.448 N, 1 inch = 25.4 mm, 1 ksi = 6.89MPa.

**Gas Fasteners in Steel**

PART NUMBER	SHANK DIA. (INCH)	TYPE OF SHANK	INSTALLED IN A36 STRUCTURAL STEEL – STEEL THICKNESS INCHES							
			ALLOWABLE LOAD – <i>Ultimate Load</i>							
			3/16 (.1875)		1/4 (.250)		3/8 (.375)			
		TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	
FPPSP916	0.104/.118	SMOOTH	-----	-----	<b>148</b> <i>744</i>	<b>157</b> <i>787</i>	<b>166</b> <i>832</i> <sup>1</sup>	<b>157</b> <i>787</i> <sup>1</sup>		

**Note 1:** ALLOWABLE loads are shown in the **LARGE BOLD** font, *Ultimate* loads are shown in *smaller italic* font. **Note 2:** Testing conducted in accordance with ICC AC70 & ASTM E1190. **Note 3:** Safety factors are based on coefficient of variation. In accordance with ICC AC70, the safety factor will be no less than 5. **Note 4:** Cyclic, fatigue, shock loads and other design criteria may require a different safety factor. **Note 5:** Job site testing may be required to determine actual job site values. **Note 6:** Values shown are for fastenings that have the entire pointed end of the fastener driven through the steel plate; except as noted below. **Note 7:** Fastener penetration is .31" minimum. **Note 8:** For SI: 1 lbf = 4.448 N, 1 inch = 25.4 mm, 1 ksi = 6.89MPa

# T4 I-F

## Compact Gas Powered Tool

*Insulation Fastening  
Innovation In A  
Smaller, Lighter,  
More Powerful  
Design.*



### SPECIFICATIONS

Part No. T4 IF-CT

Length: 20.25"

Height: 12.4"

Weight: 7.3 lbs.

Impact Force: 95J

Fuel Cell: up to 600 shots

Battery (Charged): up to 10,000 shots

### DESCRIPTION/SUGGESTED SPECIFICATIONS

#### **Fully Automatic Fastening System— IMPROVE YOUR PRODUCTIVITY - WORK FASTER THAN EVER BEFORE**

The T4 I-F System is 4 times faster than the traditional stick pin installation method. It allows the installer to attach insulation in one simple step without the use of adhesives or cutting spindle insulation anchors anymore. The latest tool in the T4 line up provides 19% more power, 7% less pushdown force, 10,000 shot battery life, all the while weighing 8% lighter than the previous model.

### ADVANTAGES

- Fasten the insulation directly to concrete, hollow block and steel studs. No need to glue and stickpin insulation anchors anymore.
- The fastening is constant and clean looking.
- Light weight of 7.3lbs means lower operator fatigue.
- The tool allows you to fasten the insulation in tight spaces through pipes and sprinkler systems.
- The T4FUEL can shoot approx. 600 shots before replacing.
- The system can be used year round; unlike stick pins, you won't be restricted by cold temperature or wet surfaces.
- Operating temperature from -15 C to 49 C
- Wide range of fasteners for 1"- 8" insulation thickness

### APPLICATIONS



- Exterior Walls - Insulation to steel
- Exterior Walls - Insulation to concrete
- Foundation Walls
- Parking Garages
- Heated Floors
- Balcony Insulation
- Block Walls
- Ceiling Acoustical Insulation



## PERFORMANCE TABLE

### STEEL STUDS

FASTENERS	ALLOWABLE/ULTIMATE PULLOUT LOAD LBS (kN)			
	22GA	20GA	18GA	16GA
T4IFS-100 - T4IFS-800	20/120 (0.09/0.53)	33/200 (0.15/0.89)	46/280 (0.20/1.25)	60/360 (0.27/1.60)

### CONCRETE

FASTENERS	CONCRETE STRENGTH PSI (Mpa)	ALLOWABLE/ULTIMATE TENSION LOADS Lbs (kN)
T4IFC-100 - T4IFC-800	3600-6500 (25-45)	35/211 (0.15/0.94)

### HOLLOW CONCRETE BLOCK

FASTENERS	ALLOWABLE/ULTIMATE TENSION LOADS Lbs (kN)
T4IFC-100 - T4IFC-800	35/184 (0.15/0.82)

## TOOL ACCESSORIES



Part No. 019903  
Battery-T4IF  
Qty: 1



Part No. 018866  
Battery Charger - T4IF  
Qty: 1



Part No. T4FUEL  
Fuel Cell - T4  
Qty: 12 (4-3 packs)

Part No. 019207  
Nose Piece - T4 I-F CT  
Qty: 1

## SELECTION CHART

### FASTENERS FOR STEEL STUDS

PART NUMBER	DESCRIPTION	INSULATION THICKNESS	BOX QTY
T4IFS-100	1" Insulation Fastener w/fuel	1" (25 mm)	500
T4IFS-112	1-1/2" Insulation Fastener w/fuel	1-1/2" (38 mm)	500
T4IFS-200	2" Insulation Fastener w/fuel	2" (50 mm)	500
T4IFS-212	2-1/2" Insulation Fastener w/fuel	2-1/2" (63 mm)	500
T4IFS-300	3" Insulation Fastener w/fuel	3" (75 mm)	500
T4IFS-312	3-1/2" Insulation Fastener w/fuel	3-1/2" (89 mm)	500
T4IFS-400	4" Insulation Fastener w/fuel	4" (100 mm)	500
T4IFS-500	5" Insulation Fastener w/fuel	5" (125 mm)	500
T4IFS-600	6" Insulation Fastener w/fuel	6" (150 mm)	400
T4IFS-700	7" Insulation Fastener w/fuel	7" (175 mm)	300
T4IFS-800	8" Insulation Fastener w/fuel	8" (200 mm)	300
T4IF	T4 I-F Insulation Tool (6" Capacity)		1
T4IF-CT	T4 I-F Compact Insulation Tool (8" Capacity)		1

### FASTENERS FOR CONCRETE AND CMU

PART NUMBER	DESCRIPTION	INSULATION THICKNESS	BOX QTY
T4IFC-100	1" Insulation Fastener w/fuel	1" (25 mm)	500
T4IFC-112	1-1/2" Insulation Fastener w/fuel	1-1/2" (38 mm)	500
T4IFC-200	2" Insulation Fastener w/fuel	2" (50 mm)	500
T4IFC-212	2-1/2" Insulation Fastener w/fuel	2-1/2" (63 mm)	500
T4IFC-300	3" Insulation Fastener w/fuel	3" (75 mm)	500
T4IFC-312	3-1/2" Insulation Fastener w/fuel	3-1/2" (89 mm)	500
T4IFC-400	4" Insulation Fastener w/fuel	4" (100 mm)	500
T4IFC-412	4-1/2" Insulation Fastener w/fuel	4-1/2" (114 mm)	500
T4IFC-500	5" Insulation Fastener w/fuel	5" (125 mm)	500
T4IFC-600	6" Insulation Fastener w/fuel	6" (150 mm)	400
T4IFC-700	7" Insulation Fastener w/fuel	7" (175 mm)	300
T4IFC-800	8" Insulation Fastener w/fuel	8" (200 mm)	300
T4IF	T4 I-F Insulation Tool (6" Capacity)		1
T4IF-CT	T4 I-F Compact Insulation Tool (8" Capacity)		1

# T4 I-F FASTENERS





## INTEGRATED THERMAL CAP

For improved thermal efficiency and aesthetics

**FLANGES** to ensure the insulation remains perfectly in place, the insulation panel won't flip around during the fastening process

**SPECIALLY SHAPED SHAFT** – Reduces friction and force required to insert fastener into insulation

**POINT** designed to pierce most difficult insulation material with little effort



Engineered curved design limits insulation compression which enables full thermal efficiency



Our C Series pin provides exceptional performance in the hardest concrete.

Our S Series pin is equipped with a 2" spiral steel stud pin which fastens insulation sheathing to exterior steel studs in one simple action.




Rockwool / Fiberglass



Expanded Polystyrene



Extruded Polystyrene



The T4 I-F Fastener™ will not spall the hollow block like powder actuated fasteners.



Damaged insulation by wind loads using stick pin fasteners. T4 I-F Fasteners™ eliminate this problem.

## FASTENER SPECIFICATIONS

- Pin Material: Heat treated carbon steel
- Pin Finish: Mechanical Zinc Plated
- Washer Material: High Density Polyethylene (HDPE)
- 2-3/8" Holding Diameter
- Made in Canada
- The fastener assembly is clearly branded Ramset along with the length of the fastener assembly



## THERMO BRIDGING



### Thermal Performance of Building Envelope Assemblies

In buildings, when insulating material is interrupted by a highly conductive material, thermal bridging takes place. Examples of thermal bridges include steel pins that interrupt the continuity of batt insulation and go through heavily insulated exterior walls. Simply put, thermal bridges occur where differences in material thermal conductivities result in significant lateral heat flow; e.g. heat flowing along the surface of a wall and then flowing through the wall via a steel pin.


The Calculations performed by the Advanced Thermal/Fluids Optimization, Modeling and Simulation (ATOMS) Laboratory, Department of Mechanical & Industrial Engineering, University of Toronto show that the Ramset T4 I-F is over 99% efficient whereas the stick pins can downgrade the efficiency by more than 10%.

### Suggested Specification

The fasteners used to attach Insulation (Rockwool, Expanded Polystyrene and Extruded Polystyrene) into Solid Masonry, Hollow Concrete Block and Steel Studs shall be a Ramset T4 I-F Fastener. The T4 I-F Fastener shall be fastened using the Ramset T4 I-F Gas Tool. The T4 I-F Fastener is made from High Density Polyethylene (HDPE) plastic and has a holding diameter of 2-3/8" (60mm) with the Ramset logo marking.



		Insulation Thickness					
		1 in	2 in	3 in	4 in	5 in	6 in
Reference	U – Factor (W/m <sup>2</sup> °C)	1.1786	0.7122	0.5103	0.3976	0.3257	0.2758
	Efficiency (%)	100.00%	100.00%	100.00%	100.00%	100.00%	100.00%
Stick Pin	U – Factor (W/m <sup>2</sup> °C)	1.2422	0.7706	0.5597	0.4397	0.3621	0.3078
	Efficiency (%)	94.88%	92.42%	91.17%	90.43%	89.94%	89.59%
InsulFast™	U – Factor (W/m <sup>2</sup> °C)	1.1845	0.7162	0.5132	0.3999	0.3276	0.2773
	Efficiency (%)	99.50%	99.45%	99.44%	99.43%	99.42%	99.42%



These thermal bridges contribute to a multitude of problems, including, but not limited to:

- Added energy use during heating and cooling seasons
- Interior surface condensation which leads to:
  - ° High humidity levels that can lead to unusual concentrations of airborne contaminants and microbial growth
  - ° Rusting issues that can damage the structure

### T4 I-F Compact Overview



Depth of drive button with 2 positions :  
DOD mini & DOD maxi

Operating temp.: -15 C to 49 C

Light-weight: Only 3.3kg with battery

Compact & light-weight lithium battery provides 10,000 shots per charge

Compact fuel cell (T4FUEL) provides approx. 600 shots

Larger gauges for battery and gas

Bi-function hook 180° rotative :  
Belt and Scaffold positions

## PIN SPECIFICATIONS

Made from AISI 1060-1065 steel. Austempered to a core hardness of 52-56 Rc  
 Typical tensile strength: 270,000 psi  
 Typical shear strength: 162,000 psi  
 Standard finish  
 - Proprietary black  
 - Mechanical zinc plate to a minimum thickness of .0002 meets requirements of ASTM B695  
 - Electroplated zinc with yellow chromate

## APPROVALS/LISTING

ICC Evaluation Service, Inc.

#ESR-1955 T3 Fasteners

## Fasteners in Concrete

FASTENER PART NUMBER	SHANK DIA. (INCH)	MINIMUM PENETRATION (INCH)	INSTALLED IN STONE AGGREGATE CONCRETE CONCRETE COMPRESSIVE STRENGTH ALLOWABLE LOAD – <i>Ultimate Load</i>						HOLLOW BLOCK Grade N, Type 1	
			4000 PSI		6000 PSI		3000 PSI Lightweight LOWER FLUTE		FACE SHELL Min 1-1/4" face thickness	
			TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)
MP034TH*	0.125	5/8	<b>78</b> 426	<b>80</b> 574	<b>62</b> 308	----	<b>72</b> 361	<b>242</b> 1210	<b>133</b> 691	----
		3/4	<b>104</b> 593	<b>195</b> 977	<b>132</b> 658	<b>206</b> 1057	<b>93</b> 470	<b>288</b> 1442	<b>84</b> 444	<b>87</b> 446
38HSMP034, 12HSMP034 TSHMP034	0.104/ .125	5/8	<b>60</b> 357	<b>117</b> 587	<b>107</b> 533	<b>191</b> 957	<b>54</b> 269	<b>230</b> 1150	<b>71</b> 357	<b>123</b> 613

\* ESR-1955 pin data applies. **Note 1:** ALLOWABLE loads are shown in the **LARGE BOLD** font, *Ultimate* loads are shown in *smaller italic* font. **Note 2:** Testing conducted in accordance with ICC AC70 & ASTM E1190  
**Note 3:** Safety factors are based on coefficient of variation. In accordance with ICC AC70, the safety factor will be no less than 5. **Note 4:** Values shown in concrete are for fastener only. Connected members must be investigated separately. **Note 5:** Cyclic, fatigue, shock loads and other design criteria may require a different safety factor. **Note 6:** Job-site testing may be required to determine actual job site values. **Note 7:** Minimum edge distance is 3 inches unless otherwise approved. In hollow block applications, no more than one fastener per cell. **Note 8:** For SI: 1 lbf = 4.448 N, 1 inch = 25.4 mm, 1 ksi = 6.89MPa.


## Intro to Powder Fastening Systems

### Over a half century of leadership in powder actuated tools and fasteners

The first powder actuated tools (PATs) were used for repairing damaged ship hulls during World War I. This application continued through World War II, when the son of the original inventor, Stanley Temple, developed and implemented the technology for commercial use. In 1947, the "Tempotool" was introduced to the construction industry.

Ramset Fasteners was founded in 1948 to handle distribution and sales for the construction trades. In 1949, Ramset's accredited Operator Program was officially launched. Today this highly successful training program has instructed over 1,000,000 trades people in the safe use of PATs.

Today, Ramset continues to bring the industry the products, service and innovation that they have come to expect from the leader in powder fastening. All geared to help contractors do their job faster, more safely and more productively.



# Training and Certification

## DESCRIPTION

Ramset has designed and engineered the right powder actuated tool for your applications. To ensure you use a powder actuated tool correctly, please take the time to review the Operator's Safety and Operating Instruction Manual packaged with each tool. These manuals are also available for download on the Ramset website.

To assure safety on the jobsite, OSHA and ANSI require that all powder actuated tool users become trained and certified for the particular tool being used. One way Ramset enables you to receive this training is through our website training program. This innovative approach to education combines interactive web-based training techniques and online testing with immediate feedback to provide you a rich learning environment.

The course consists of approximately 30 pages of usage, safety and troubleshooting material.

Upon completion of this brief course you will have the opportunity to take an online exam. Instructions for taking these exams are provided at the end of the course. With successful completion of the exam, you have the opportunity to print a certification card.

As an industry leader in powder actuated fastening systems, Ramset continues to provide the most effective and comprehensive instructor and operator training programs available.

**POWDER ACTUATED TOOL LICENSING EXAM**

**Test Fastening**

Always make a test fastening using the lowest power level recommended for the particular tool. The chart on this page represents the Powder Load Identification by both color and number. Later in this course you will be asked to perform an exercise demonstrating that you can identify these loads.

It is also important that the test fastening is made after being sure that the base material is suitable for powder-actuated fastening. To do this, perform a Center Punch Test.

**Powder Load Identification**

POWER LEVEL	LOAD COLOR	LOWER POWER
1	GRAY	↓ HIGHER POWER
2	BROWN	
3	GREEN	
4	YELLOW	
5	RED	
6	PURPLE	

**Learning Bytes**

**Ramset**  
POWDER FASTENING SYSTEMS

10 of 27

**POWDER ACTUATED TOOL LICENSING EXAM**

**Safety Goggles and Hearing Protection**

Safety practices are very important when using the Ramset Powder Actuated tools. **Always wear safety goggles and hearing protection.**

- Failure to wear safety goggles may result in serious eye injury from flying debris.
- Constant or repeated unprotected exposure to fastening noise may cause permanent hearing loss.

**Ramset**  
POWDER FASTENING SYSTEMS

1 of 27

**POWDER ACTUATED TOOL LICENSING EXAM**

**Proper Storage**

To prevent use of a powder actuated tool by unlicensed individual, always store the tool unloaded and keep the tool and the loads securely locked in a tool box.

**Ramset**  
POWDER FASTENING SYSTEMS

5 of 27

Visit [ramset.ca](http://ramset.ca) for online PAT licensing

# RA27 Fully Automatic P.A.T.

**.27 Caliber Strip Tool**  
**Fully-Automatic**  
**1-1/2" Pin Capacity**  
**(2" w/washer)**



## ACCESSORIES



Magazine Part Number: RA27MAG  
Weight: 1.3 lbs  
Maximum pin length: 1-1/4" Collated True Embedment only (TE\_X) pins

## DESCRIPTION/SUGGESTED SPECIFICATIONS

### Fully-Automatic Strip Tool—

#### MOST COMMON APPLICATION DRYWALL TRACK TO CONCRETE!

Ramset's fully automatic RA27 powder-actuated tool lowers downtime and fatigue on commercial job sites. The RA27 stands up to the toughest use for interior and exterior applications. The RA-27 magazine attachment (P/N RA27MAG - sold separately) shoots Ramset's collated true embedment pins.

## ADVANTAGES

- Lower pushdown force reduces fatigue
- Long-lasting piston reduces downtime
- Collar requires only ¼ turn for quicker cleaning
- More power load-for-load provides flexibility in a wide range of applications
- Power adjust dial provides the ability to dial down power for ideal pin embedment
- Patented RBC (Residue Build-up Channel) allows user to work longer between cleanings
- Back end padding absorbs recoil, reducing fatigue
- Belt/tether clip for safety
- Swivel lift/scaffold hook keeps the tool within reach at all times

## MOST COMMON FASTENERS

PIN #	PIN LENGTH		MOST COMMON APPLICATION
	IN.	MM	
1512SD	1-1/2	38.1	Fasten with increased bearing surface against material to be fastened
SP12	1/2	12.7	Drywall track to structural steel
1506	3/4	19.1	Drywall track to concrete

See pages R 35 - R 36 for all fasteners.

## COLLATED TRUE EMBEDMENT PINS

10-Pin Collated Stips for the Ramset RA27 with RA27MAG and other brands

PART #	PIN LENGTH		EMBEDMENT LENGTH	
	IN.	MM	IN.	MM
TE12X	9/16	13.84	1/2	12.7
TE34X	13/16	20.6	3/4	19.1
TE100X	1-1/16	27.05	1	25.4
TE114X	1-5/16	33.3	1-1/4	31.8

Shank diameter = .157 Head diameter = .320

## SPECIFICATIONS

Tool Part No. RA27

.27 caliber 10-shot strip loads 3, 4, 5

Weight: 5.3 pounds

Length: 15"

Muzzle Bushing O.D.: 9/16"

Maximum Pin Length: 1-1/2" (2" w/washer)

3 year warranty

### POWER LEVEL GUIDE FOR LOADS


All loads are color coded and load level numbered. As the number increases, the power level increases.

Always start with the lightest load. If the fastener does not set completely, use the next higher load and repeat the process.



# Cobra+

**.27 Caliber Strip Tool**  
**Semi-Automatic**  
**2-1/2" Pin Capacity**  
**(3" w/washer)**



## DESCRIPTION/SUGGESTED SPECIFICATIONS

### Semi-Automatic Strip Tool—

#### MOST COMMON APPLICATION DRYWALL TRACK TO CONCRETE!

The Cobra+ can be used in different applications, a few are electrical junction boxes to steel or concrete, door and window frames to concrete, HVAC duct straps and forming work.

## ADVANTAGES

- Semi-automatic .27-caliber tool —uses strip loads
- Padded recoil-absorbing handle—for greater operator comfort
- Power adjustable for maximum efficiency
- Silencer that reduces noises by 30%
- Ergonomic handle maximizes user comfort
- Fastens up to 3" standard Ramset drive pins and threaded studs—ideal for general construction applications
- Full one-year warranty

## MOST COMMON FASTENERS

PIN #	PIN LENGTH		MOST COMMON APPLICATION
	IN.	MM	
1524SDP (washed)	3	76.2	2" x 4" to concrete
1516SDC (washed)	2-1/2	63.5	2" x 4" to concrete
1506	3/4	19.1	Drywall track to concrete

See pages R 35 - R 36 for all fasteners.

## SPECIFICATIONS

Part No. COBRA+

.27 caliber 10-shot strip loads 2, 3, 4, 5

Weight: 5.25 pounds

Length: 15"


Muzzle Bushing O.D.: 9/16"

Maximum Pin Length: 3"

### POWER LEVEL GUIDE FOR LOADS

All loads are color coded and load level numbered. As the number increases, the power level increases.

Always start with the lightest load. If the fastener does not set completely, use the next higher load and repeat the process.



# Cobra+ InsulFast with Cobra+ conversion kit

**Ramset's Semi-Automatic Powder Actuated Option for Insulation Fastening**  
**Easy and Convenient Kit to Maximize Productivity**



COBRAIFKIT Conversion Kit

## DESCRIPTION/SUGGESTED SPECIFICATIONS

### *Semi-Automatic Strip Tool for Fastening Insulation to Concrete*

**MAXIMIZE YOUR PRODUCTIVITY AND COVER 2 APPLICATIONS WITH THE SAME TOOL!**

The Cobra+ InsulFast Conversion Kit allows for an easy and convenient way to tackle 2 applications with the same great Cobra+ tool. Used it for your typical PAT application as well as for fastening rigid and semi-rigid insulation to concrete.

## ADVANTAGES

- Fasten insulation to concrete up to 4X faster than traditional methods
- Convert your tool back and forth in less than 5 minutes
- Reduce heat loss/thermal bridging of common metal fasteners with InsulFast fasteners. See page R 16 for more info



## SELECTION CHART

PART NUMBER	DESCRIPTION	INSULATION THICKNESS	QUANTITY PER BOX
COBRA+	Semi Automatic Strip Tool, 27 CAL	-	1
COBRAIFKIT	Cobra+ IF Conversion Kit	-	1
IG625PAT*	1" InsulFast Fasteners with Green Powder Loads Incl.	1" (25 mm)	100
IG638PAT*	1-1/2" InsulFast Fasteners with Green Powder Loads Incl.	1-1/2" (38 mm)	100
IG650PAT*	2" InsulFast Fasteners with Green Powder Loads Incl.	2" (50 mm)	100

\* Other fastener lengths available on special request

\* For more information on InsulFast fasteners see page R 16 and R 18, for more information on Cobra+ tool see page R 24

## SPECIFICATIONS

Part No. COBRA+

.27 caliber 10-shot strip loads 2, 3, 4, 5

Weight: 5.25 pounds

Length: 15"

Part No. COBRAIFKIT

Includes: Piston assembly (P/N 585810), Pin guide (P/N 585821), Buffer (P/N 585822), and detailed installation instructions.

# .22 Cal Single Shot Tools

## HammerShot 22 Cal



## MasterShot 22 Cal



## TriggerShot 22 Cal



### DESCRIPTION/SUGGESTED SPECIFICATIONS

#### Single Shot - Hammer Activation Tool—

The Ramset HammerShot .22 Caliber Single Shot Tool is a hammer-actuated tool utilizing .22 caliber loads. This tool is great for small DIY projects. The HammerShot can easily fasten up to 2-1/2 in. drive pins.

### ADVANTAGES

- For small DIY projects, such as fastening two by fours and furring strips to concrete in basements or room additions
- Hammer-actuated tool with a barrel design that allows for easy horizontal and overhead fastening, up to 2-1/2 in. drive pins

### SPECIFICATIONS

Part No. 45000  
.22 caliber single shot loads 2,3,4  
Actuated Tool Type: Load/Booster

### DESCRIPTION/SUGGESTED SPECIFICATIONS

#### Single Shot Tool - Sound Suppression Technology

##### CAN FASTEN UP TO 3 INCH DRIVE PINS WITH WASHER

Designed for frequent use providing fastening results in a variety of concrete, masonry or steel applications.

- Noise-reducing design up to 30% quieter
- Powder load automatically ejects after each use.

### ADVANTAGES

- For light and medium duty applications in concrete and steel
- Ideal for attaching 2 x 4s, furring strips and electrical boxes
- 90 Day Warranty
- Heavy-duty all-steel construction

### SPECIFICATIONS

Part No. 45100  
.22 caliber single shot loads 2,3,4  
Weight: 4.1 pounds  
Maximum Pin Length: 2-1/2" (3" w/washer)

### DESCRIPTION/SUGGESTED SPECIFICATIONS

#### Single Shot - Trigger Activation —

For small DIY projects, such as fastening two by fours and furring strips to concrete in basements or room additions.

### ADVANTAGES

- Trigger Actuated, No Hammer Required!
- For fastening to concrete, masonry or steel

### SPECIFICATIONS

Part No. 45200  
.22 caliber single shot loads 2,3,4  
Weight: 3.7 pounds  
Maximum Pin Length: 2-1/2" (3" w/washer)

## FASTENERS – HOW THEY WORK

### DESCRIPTION

#### FASTENING TO CONCRETE

As the fastener enters the concrete, extreme pressures and heat are created. This creates a bond that provides high loading strength in concrete.

#### FASTENING TO STEEL

The resilience of steel provides a clamping effect to the fastener. This combined with the tremendous heat that is created, provides a welding and clamping effect to give maximum holding power.

### FASTENING PLACEMENT AND PENETRATION

The following represents the minimum edge and spacing requirements, plus base material thickness requirements:

#### CONCRETE

- Edge distance.** Do not fasten closer than 3 inches from the edge of concrete. If the concrete cracks, the fastener may not hold and may allow the fastener to ricochet, causing serious injury or death to the operator or bystanders.
- Recommended minimum fastener spacing.** Setting fasteners too close together can cause the concrete to crack. The recommended MINIMUM DISTANCE between fastening is three (3) inches. Never attempt a fastener application too close to another previously inserted fastener to prevent the second fastener from ricocheting off the previously installed fastener. A ricochet can result in serious injury or death to the operator or bystanders.

- Concrete thickness.** It is important that the concrete be at least three (3) times as thick as the fastener penetration. If the concrete is too thin, the compressive forces forming at the fastener's point can cause the free face of the concrete to break away. This creates a dangerous condition from flying concrete and/or the fastener and also results in a reduction of fastener holding power.

#### STEEL



- Edge distance.** The recommended edge distance for a fastener to the edge of steel is 1/2 inch. Never fire the tool within 1/2 inch of the edge of a steel base material because the steel may bend or break off, allowing the fastener to ricochet, causing serious injury or death to the operator or bystanders.
- Recommended minimum fastener spacing.** The recommended minimum distance between fastening is 1 inch. Never attempt a fastening application too close to another previously inserted fastener to prevent the second fastener from ricocheting off the previously installed fastener. A ricochet can result in serious injury or death to the operator or bystanders.
- Steel thickness.** Do not fasten into steel base material thinner than the fastener shank diameter. Holding power will be reduced and the fastener may be over-driven, creating a dangerous situation to the operator or bystanders due to a free-flying fastener.

### HOW TO SELECT A POWDER ACTUATED FASTENER



**Drive pins** are used to directly fasten an object (permanent installation). **Threaded studs** are used where the object fastened is to be removed or where shimming is required. The following shows how to determine shank and thread length. Required penetration is determined by load requirement (illustrated in the following examples).

Ramset fasteners may be specified by their type or catalog number to satisfy fastening requirements.

#### Permanent Installation




#### Removable Installation



# Fasteners – How They Work

## SELECTING THE CORRECT FASTENER LENGTH



High quality fasteners provide consistent and reliable performance in concrete, block, masonry, and steel applications. Choosing the correct fastener for the job will assure professional results.

- A** Determine thickness of material being attached.
- B** Fastener must be long enough to drive approximately 1" into concrete, cement block or penetrate thickness of steel.

## POWER LEVEL GUIDE FOR LOADS

All loads are color coded and load level numbered. As the number increases, the power level increases.

*Always start with the lightest load. If the fastener does not set completely, use the next higher load and repeat the process.*




## TYPICAL USES

### WOOD ATTACHMENT\*

### CONCRETE BASE MATERIAL


### STRUCTURAL STEEL BASE



	COMMONLY USED FASTENER		COMMONLY USED LOAD		COMMONLY USED FASTENER		COMMONLY USED LOAD	
2 X 4	1516	(2-1/2")	YELLOW #4		SP178	(1-7/8")	RED #5	
3/4" Plywood for furring strip	1512	(1-1/2")	GREEN #3		1510	(1-1/4")	YELLOW #4	
1/4" – 1/2" Plywood	1512	(1-1/2")	GREEN #3		1506	(3/4")	YELLOW #4	

\* USE RAMGUARD PIN FOR TREATED LUMBER. SEE PAGE 30.

### THIN GAGE STEEL



<b>Electrical</b>								
Junction Boxes	1508	(1")	GREEN #3		SP58TH	(5/8")	YELLOW #4	
Shelf Brackets	1508	(1")	GREEN #3		1506	(3/4")	YELLOW #4	
<b>Interior</b>								
Drywall Track	1506	(3/4")	BROWN #2		1503K	(1/2")	YELLOW #4	
<b>Perimeter</b>								
Track	1510	(1-1/4")	YELLOW #4		1503K	(1/2")	YELLOW #4	


**NOTE** This chart is presented as a guide only. Start with the lightest load. If the fastener does not set completely, use the next higher load and repeat the process. Product suggestions may not be suitable for all types of base materials. Contact Technical Services if you have further questions.

# Troubleshooting

## CONCRETE

### SYMPTOM

**FASTENER DOES NOT HOLD IN BASE MATERIAL OR BASE MATERIAL SPALLS**




### CAUSE

- | High strength concrete
- | Hard or large aggregate in concrete

### ACTION

- | Use shorter fastener
- | Use PowerPoint pin
- | Use load with a different power level

**FASTENER PENETRATES TOO DEEP**




### CAUSE

- | Fastener too short for application
- | Tool power level too high

### ACTION

- | Use longer fastener
- | Use a lighter powder load

**FASTENER DOES NOT PENETRATE DEEP ENOUGH**




### CAUSE

- | Fastener too long
- | Tool power level too low

### ACTION

- | Use a shorter fastener
- | Use a stronger powder load

**FASTENER BENDS**



### CAUSE

- | Fastener hit large aggregate on entry
- | Concrete too hard
- | Fastener hit rebar just under the surface


### ACTION

- | Use shorter fastener
- | Use PowerPoint pin
- | Make sure tool is perpendicular to the work surface
- | Move over 3 inches, try to fasten again

## STEEL

### SYMPTOM

**FASTENER DOES NOT PENETRATE THE SURFACE**




### CAUSE

- | Driving power too low
- | Material may be too hard for forced entry fastener

### ACTION

- | Increase powder load level
- | Use PowerPoint pin

**FASTENER DOES NOT HOLD IN BASE MATERIAL**




### CAUSE

- | Steel base material is too thin

### ACTION

- | Use gas system tools with smaller Shank pin or Tek pin

**FASTENER BREAKS OR BENDS**




### CAUSE

- | Driving power is too low
- | Fastener is too long
- | Material may be too hard for forced entry fastener

### ACTION

- | Increase powder load level
- | Reduce fastener length

**FASTENER DOES NOT FULLY PENETRATE STEEL**



### CAUSE

- | Driving power too low
- | Steel base material too thick
- | Application limit may have been reached

### ACTION

- | Increase powder load level
- | Use PowerPoint pin

# Problem Solving Pins

## PowerPoint Pins for Hard Concrete & Steel Fastening



### DESCRIPTION/SUGGESTED SPECIFICATIONS


Use Ramset's exclusive PowerPoint pins for your advanced fastening applications. They provide easier penetration into hard steel and concrete. That means reduced pin failures and increased holding values to make your jobs more productive.

### ADVANTAGES

#### Consistent Performance, in Hard Steel and Hard Concrete

Standard powder actuated pins fasten inconsistently in steel. Frequently the steel is just too hard for conventional pins. Steel is also inconsistent because hardness varies. According to the steel industry's accepted Rockwell Hardness Scale (Rb), steel strength can vary from a relatively soft 54 Rb to an extremely hard 88 Rb or higher. Standard pins typically begin to fail in the upper 70s Rb. Tests, however, have proven that PowerPoint consistently performs, even as steel approaches 90 Rb!

**AVERAGE IN PLACE FASTENER COSTS**



Notice in the photographs below how typical manufacturing processes can cause inconsistency in a pin's finish, increasing its likelihood of failure. And see the difference with Ramset's process! Which pin would you want to use?

Ramset's unique manufacturing process results in uniform shape and finish for more consistent performance.

Typical cut-point finish resulting from manufacturing process will increase pin failure

Typical swage-ballistic point finish results in potential failure of pin

### SELECTION CHART

MATERIAL	BASE STEEL THICKNESS				
	3/16"	1/4"	3/8"	1/2"	3/4"
2' x 4' Plate	SP178	SP178	SP178	SP178	SP178
13 Ga. to 17 Ga.	SP12				
18 Ga. to 25 Ga.	SP12				



See page R 35 for fastener selection.

#### Ramguard™ Drive Pins for ACQ Pressure Treated Lumber!

As many of you know, there have been changes to the regulations affecting pressure treated lumber. The industry standard CCA treated wood is no longer being produced for residential use. Most new pressure treated wood is utilizing Alkaline Copper Quaternary (ACQ) treatment. It has been confirmed that ACQ corrodes steel 2 to 4 times faster than the old CCA treated lumber. This means that our standard drive pins are not recommended for use in ACQ treated lumber.

Ramset has developed a coating called Ramguard™ for use in all pressure treated wood including the new ACQ treated wood. The Ramguard coating offers excellent corrosion resistance that rivals hot dipped galvanized and stainless steel. Washered versions of these pins utilize a Ramguard coated pin and a washer with a G185 coating. This combination was developed to withstand the increased corrosion rate that sometimes occurs when using fasteners in the new treated lumber.

# POWDER FASTENERS

## DESCRIPTION

We maintain only the highest standards in the materials, production techniques and quality control measures used to manufacture our fasteners, assuring consistent, optimum quality in every fastener.

## ADVANTAGES

### BLACK PINS

The special black coating improves pin penetration into difficult base material (i.e. hard concrete). We offer this black coating on all of our fasteners manufactured for the attachment of drywall track and channel to concrete and steel.

### PINS

ITW Ramset powder actuated fasteners are specifically fabricated to meet the exacting requirements of toughness and durability that enable them to penetrate dense concrete and structural quality steel.

### FASTENER TERMINOLOGY SUFFIX

- K = Knurled
- B = Black
- E = Ramguard
- X = Collated
- SD = Washer
- C = 100 count
- M = 1000 count

## Plated Drive Pins

Designed for use in concrete and structural steel applications.  
 100 per box.



PART NUMBER	SHANK LENGTH IN. (MM)	BOX QTY	MASTER CASE QTY	ROCKET	XT540	SA270/TS750P	RAZ7	COBRA	D45/D45A	D60	721	RS22/HD22	DX 351	DX 36	DX 350	DX 460	DX A40	DX A41	DX 35	DX E72	
1503K	1/2 Knurled (12.7)	100	5,000																		
1506	3/4 (19.1)	100	1,200																		
1508	1 (25.4)	100	1,200																		
1510	1-1/4 (31.8)	100	1,000																		
1512	1-1/2 (38.1)	100	1,200																		
1514	2 (50.8)	100	800																		
1516	2-1/2 (63.5)	100	800																		
1524	3 (76.2)	100	600																		

Shank diameter = .145 Head diameter = .300

## Plated Drive Pins (25 Packs)

Designed for use in concrete and structural steel applications.




PART NUMBER	SHANK LENGTH IN. (MM)	BOX QTY	MASTER CASE QTY	ROCKET	XT540	SA270/TS750P	RAZ7	COBRA	D45/D45A	D60	721	RS22/HD22	DX 351	DX 36	DX 350	DX 460	DX A40	DX A41	DX 35	DX E72	
R50122	1-1/2 (38.1)	25	125																		
R50124	2 (50.8)	25	125																		
R50126	2-1/2 (63.5)	25	125																		
R50128	Multi Pack	200	1,000																		

Shank diameter = .145 Head diameter = .300

## Plated Drive Pins with 7/8" Washer

Washer increases bearing surface against the material to be fastened. 100 per box. 16 gage metal washer.



PART NUMBER	SHANK LENGTH IN. (MM)	BOX QTY	MASTER CASE QTY	ROCKET	XT540	SA270/TS750P	RAZ7	COBRA	D45/D45A	D60	721	RS22/HD22	DX 351	DX 36	DX 350	DX 460	DX A40	DX A41	DX 35	DX E72	
1508SD	1 (25.4)	100	1,000																		
1510SD	1-1/4 (31.8)	100	1,000																		
1512SD	1-1/2 (38.1)	100	1,000																		
1516SDC	2-1/2 (63.5)	100	600																		
1524SDP*	3 (76.2)	100	600																		

Shank diameter = .145 Head diameter = .300 \* Square washer indicates 3" pin has been installed.

# Powder Fasteners

## PowerPoint Step Shank Pins

Used for fastening into hard concrete and steel. Premium hard concrete and steel pin. 100 per box.



PART NUMBER	SHANK LENGTH IN. (MM)	BOX QTY	MASTER CASE QTY	ROCKET	XT540	SA270/TS750P	RA27	COBRA	D45/D45A	D60	721	RS22/HD22	DX351	DX36	DX350	DX460	DXA40	DXA41	DX35	DXE72	
SP12*	1/2 (12.7)	100	1,200	■	■	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■
SP178	1-7/8 (47.6)	100	1,000	■		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

Shank diameter = .150/.180

Head diameter = .300

\* Shank diameter = .150, Regular PowerPoint pin without Step Shank.

## Top Hat Drive Pins

Increases bearing surface against material to be fastened for improved attachment to inconsistent base materials. 100 per box.



PART NUMBER	SHANK LENGTH IN. (MM)	BOX QTY	MASTER CASE QTY	ROCKET	XT540	SA270/TS750P	RA27	COBRA	D45/D45A	D60	721	RS22/HD22	DX351	DX36	DX350	DX460	DXA40	DXA41	DX35	DXE72	
SP58TH	5/8 (15.9)	50	5,000	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

Shank diameter SP58TH and SP34TH = .150

1906 and 1908 = .145

Head diameter = .300

## Ramguard Pins

Coated to improve corrosion resistance in treated lumber and other applications. 100 per box.



PART NUMBER	SHANK LENGTH IN. (MM)	BOX QTY	MASTER CASE QTY	ROCKET	XT540	SA270/TS750P	COBRA	D45/D45A	D60	721	RS22/HD22	DX351	DX36	DX350	DX460	DXA40	DXA41	DX35	DXE72	
1516E	2-1/2 (63.5)	100	800		■	■	■				■		■	■	■		■			■
15245DE*	3 (76.2)	100	600		■	■	■				■				■		■			■

Shank diameter = .145 \* .150/.180

Head diameter = .300

## Fastener Ceiling Clips

14 gage angle clip. 100 clips per box.



PART NUMBER	DESCRIPTION
1202CF	Angle clip (no pin)

Hole diameter: 5/16" & 14/64"

## True Embedment Pins

10-Pin Collated Strips for the Ramset RA27 with RA27MAG and other brands

PART NUMBER	BOX QTY	MASTER CASE QTY	RA27 (with magazine)	XT540 (with magazine)
TE12X	1,000	5,000	■	■
TE34X	1,000	5,000	■	■
TE100X	1,000	5,000	■	■
TE114X	1,000	5,000	■	■


Hole diameter: 5/16" & 14/64" Shank diameter = .157 Head diameter = .320

# Powder Loads

High Quality and Dependability



CW Series



RS27 Series

## DESCRIPTION/SUGGESTED SPECIFICATIONS

ITW Ramset powder loads and tools match tolerances to provide optimum power within recognized national velocity standards. Available in color-coded 10-load discs, 10-load strips and 100-load boxes.

**Caution:** Always test-fasten with the lowest power level for your tool. If more power is necessary, use the next highest power level until proper level and fastening is achieved. Refer to the operator's manual for more specific details. Observe all safety reminders. Tool operators must be trained and qualified as required by federal law. Failure to use properly can result in serious injury or death to users or bystanders.

### Advantages Powder Guide

Power level is designated by the load level number marked on each box and by the color of the box and each powder load. As the number increases, the power level increases.

### POWER LEVEL GUIDE FOR LOADS

All loads are color coded and load level numbered. As the number increases, the power level increases.



Always start with the lightest load. If the fastener does not set completely, use the next higher load and repeat the process.

## SELECTION CHART

### 0.22 CALIBER, SINGLE SHOT LOAD

PART NUMBER	POWER LEVEL-COLOR	721	M70	HD22 RS22	DXE37	DXE72	BOX QTY WT (LBS)	CASE QTY WT (LBS)
C22CW	2 - Brown	■	■	■	■	■	100/0.2	1,200/2.4
C32CW	3 - Green	■	■	■	■	■	100/0.2	1,200/2.4
C42CW	4 - Yellow	■	■	■	■	■	100/0.2	1,200/2.4

### 0.22 CALIBER, SINGLE SHOT LOAD (25 PACKS)


PART NUMBER	POWER LEVEL-COLOR	721	M70	HD22 RS22	DXE37	DXE72	BOX QTY WT	CASE QTY WT
R50116	3 - Green	■	■	■	■	■	25	125
R50118	4 - Yellow	■	■	■	■	■	25	125

### 10-SHOT, 0.27 CALIBER, STRIP LOAD

PART NUMBER	POWER LEVEL-COLOR	ROCKET	RA27	COBRA+	COBRA III	SAZ70 TS750P	XT540	DX36M	DX350	DX351	DX450	DX460	DXA40	DXA41	BOX QTY WT (LBS)	CASE QTY WT (LBS)
C3RS27	3 - Green	■	■	■	■	■	■	■	■	■	■	■	■	■	100/0.3	600/1.8
C4RS27	4 - Yellow	■	■	■	■	■	■	■	■	■	■	■	■	■	100/0.3	600/1.8
C5RS27	5 - Red	■	■	■	■	■	■	■	■	■	■	■	■	■	100/0.3	600/1.8

## SUGGESTED SPECIFICATIONS

*Ramset provides the architect and engineer, the following suggested language and helpful information for the purpose of fastening specifications.*



**Track or Clip to Steel Beam**

**Part Number SP58TH**

Fasteners used shall be designated power point type with a 0.150 nominal shank diameter and a length of 5/8 inches.

**Interior Partition Track to Concrete**

**Part Number T3034B**

Fasteners used shall be designated "T3" type with a 0.125 nominal shank diameter and 3/4 inch embedment depth.

**Exterior Perimeter Track to Concrete**

**Part Number SP178**

Fastener used shall have a 0.150/0.180 shank diameter and a length of 1-7/8"

**For assistance with specifications and/or substitutions, contact Technical Service at 800-387-9692.**

## POWDER PERFORMANCE/SUBMITTAL

**Ramset fasteners may be specified by their type or catalog number to satisfy fastening requirements.**

### PIN SPECIFICATIONS

Made from AISI 1060-1065 steel. Austempered to a core hardness of 52-56 Rc  
 Typical tensile strength: 270,000 psi  
 Typical shear strength: 162,000 psi  
 Standard finish  
 - Proprietary black  
 - Mechanical zinc plate to a minimum thickness of .0002 meets requirements of ASTM B695

### APPROVALS/LISTING

ICC Evaluation Service, Inc.

#ER-1147 Sill Plate

#ESR-1799 Powder Pins & Clips

City of Los Angeles

#RR-22668 Powder pins

### PERFORMANCE TABLES

#### Fasteners in Normal Weight Concrete

PART NUMBER SERIES	SHANK DIAMETER (INCH)	MINIMUM PENETRATION (INCH)	INSTALLED IN STONE AGGREGATE CONCRETE CONCRETE COMPRESSIVE STRENGTH ALLOWABLE LOAD – <i>Ultimate Load</i>							
			2000 PSI				4000 PSI		6000 PSI	
			TENSION (LBS)		SHEAR (LBS)		TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)
1500/ 1600 SERIES	0.145	3/4	<b>50</b> <i>655</i>	<b>66</b> <i>739</i>	<b>100</b> <i>511</i>	<b>104</b> <i>552</i>	-----	-----	-----	-----
		1	<b>152</b> <i>943</i>	<b>166</b> <i>1229</i>	<b>157</b> <i>937</i>	<b>182</b> <i>1342</i>	-----	-----	-----	-----
		1-1/4	<b>159</b> <i>1078</i>	<b>265</b> <i>1665</i>	<b>179</b> <i>1043</i>	<b>267</b> <i>1538</i>	-----	-----	-----	-----
		1-1/2	<b>154</b> <i>1450</i>	<b>340</b> <i>2027</i>	<b>209</b> <i>1357</i>	<b>342</b> <i>1712</i>	-----	-----	-----	-----
SP	0.150	3/4	-----	-----	<b>150</b> <i>803</i>	<b>105</b> <i>786</i>	<b>81</b> <i>493</i>	<b>82</b> <i>454</i>	-----	-----
SP SERIES	.150/.180	1	<b>154</b> <i>1043</i>	<b>200</b> <i>1173</i>	<b>243</b> <i>1307</i>	<b>175</b> <i>1037</i>	<b>189</b> <i>1125</i>	<b>210</b> <i>1177</i>	-----	-----
		1-1/4	<b>207</b> <i>1553</i>	<b>230</b> <i>1636</i>	<b>298</b> <i>1749</i>	<b>218</b> <i>1471</i>	<b>213</b> <i>1568</i>	<b>305</b> <i>1780</i>	-----	-----
		1-1/2	-----	-----	<b>384</b> <i>2126</i>	<b>391</b> <i>1957</i>	<b>239</b> <i>1886</i>	<b>594</b> <i>2968</i>	-----	-----
3300 SERIES	0.180	1	<b>196</b> <i>1084</i>	<b>100</b> <i>1328</i>	<b>255</b> <i>1504</i>	<b>284</b> <i>1557</i>	-----	-----	-----	-----
		1-1/4	<b>241</b> <i>1207</i>	<b>329</b> <i>1710</i>	<b>294</b> <i>1574</i>	<b>373</b> <i>2104</i>	-----	-----	-----	-----
		1-1/2	<b>254</b> <i>1601</i>	<b>379</b> <i>1971</i>	<b>419</b> <i>2239</i>	<b>501</b> <i>2505</i>	-----	-----	-----	-----
1900	0.145	3/4	<b>105</b> <i>694</i>	<b>71</b> <i>458</i>	<b>101</b> <i>685</i>	<b>99</b> <i>627</i>	-----	-----	-----	-----
9100 STUD	0.205	1	<b>187</b> <i>988</i>	<b>212</b> <i>1385</i>	<b>186</b> <i>1070</i>	<b>303</b> <i>1618</i>	-----	-----	-----	-----
		1-1/4	<b>262</b> <i>1450</i>	<b>304</b> <i>1674</i>	<b>335</b> <i>2161</i>	<b>400</b> <i>2000</i>	-----	-----	-----	-----

**Note 1:** ALLOWABLE loads are shown in the **LARGE BOLD** font, *Ultimate* loads are shown in *smaller italic* font. **Note 2:** Testing conducted in accordance with ICC AC70 & ASTM E1190. **Note 3:** Safety factors are based on coefficient of variation. In accordance with ICC AC70, the safety factor will be no less than 5. **Note 4:** Values shown in concrete are for the fastener only. Connected members must be investigated separately. **Note 5:** Cyclic, fatigue, shock loads, and other design criteria may require a different safety factor. **Note 6:** Job site testing may be required to determine actual job site values. **Note 7:** Minimum edge distance is 3 inches unless otherwise approved. **Note 8:** For SI: 1 lbf = 4.448 N, 1 inch = 25.4 mm, 1 ksi = 6.89MPa

## PERFORMANCE TABLES

### Fasteners in Steel

PART NUMBER SERIES	SHANK DIA. (INCH)	TYPE OF SHANK	INSTALLED IN A36 STRUCTURAL STEEL—STEEL THICKNESS (INCHES)									
			ALLOWABLE LOAD – <i>Ultimate Load</i>									
			3/16		1/4		3/8		1/2		3/4	
		TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	
1500/1600	0.145	SMOOTH	<b>81</b> <i>790</i>	<b>373</b> <i>2039</i>	<b>181</b> <i>1269</i>	<b>273</b> <i>1642</i>	<b>397</b> <i>2169</i>	<b>489</b> <i>2771</i>	<b>243</b> <i>1328<sup>8</sup></i>	<b>277</b> <i>1514<sup>8</sup></i>	----	----
		KNURLED	<b>296</b> <i>1633</i>	<b>636</b> <i>3516</i>	<b>584</b> <i>3384</i>	<b>659</b> <i>3822</i>	<b>680</b> <i>3755</i>	<b>730</b> <i>4030</i>	<b>253</b> <i>1459<sup>8</sup></i>	<b>293</b> <i>1632<sup>8</sup></i>	----	----
SP	0.150	SMOOTH	<b>385</b> <i>2107</i>	<b>662</b> <i>3618</i>	<b>445</b> <i>2549</i>	<b>477</b> <i>2736</i>	<b>393</b> <i>2145</i>	<b>574</b> <i>3137</i>	<b>948</b> <i>5180</i>	<b>597</b> <i>3500</i>	<b>234</b> <i>1244<sup>8</sup></i>	<b>356</b> <i>1895<sup>8</sup></i>
3300	0.180	SMOOTH	<b>281</b> <i>1536</i>	<b>580</b> <i>3169</i>	<b>385</b> <i>2212</i>	<b>507</b> <i>2931</i>	<b>460</b> <i>2631</i>	<b>644</b> <i>3518</i>	<b>641</b> <i>3499</i>	<b>684</b> <i>3739</i>	----	----
9100	0.205	KNURLED	<b>160</b> <i>1469</i>	<b>931</b> <i>5084</i>	<b>350</b> <i>3115</i>	<b>617</b> <i>3542</i>	<b>843</b> <i>4605</i>	<b>803</b> <i>4391</i>	<b>565</b> <i>3086<sup>9</sup></i>	<b>547</b> <i>3373<sup>9</sup></i>	----	----

PART NUMBER SERIES	SHANK DIA. (INCH)	TYPE OF SHANK	INSTALLED IN A572 GRADE 50 STRUCTURAL STEEL—STEEL THICKNESS (INCHES)									
			ALLOWABLE LOAD – <i>Ultimate Load</i>									
			3/16		1/4		3/8		1/2		3/4	
		TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	
1500/1600	0.145	SMOOTH	----	----	----	----	----	----	----	----	----	----
		KNURLED	<b>260</b> <i>1609</i>	<b>499</b> <i>3182</i>	<b>579</b> <i>3411</i>	<b>725</b> <i>4272</i>	<b>383</b> <i>2216<sup>7</sup></i>	<b>595</b> <i>3431<sup>7</sup></i>	----	----	----	----
SP	0.150	SMOOTH	<b>356</b> <i>2123</i>	<b>569</b> <i>3394</i>	<b>554</b> <i>3232</i>	<b>637</b> <i>3710</i>	<b>604</b> <i>3447</i>	<b>602</b> <i>3437</i>	<b>814</b> <i>4473<sup>9</sup></i>	<b>820</b> <i>4503<sup>9</sup></i>	<b>243</b> <i>1362<sup>8</sup></i>	<b>381</b> <i>2141<sup>8</sup></i>
3300	0.180	SMOOTH	----	----	----	----	----	----	----	----	----	----
9100	0.205	KNURLED	<b>365</b> <i>2175</i>	<b>903</b> <i>5385</i>	<b>697</b> <i>4061</i>	<b>907</b> <i>5285</i>	<b>155</b> <i>842<sup>7</sup></i>	<b>376</b> <i>2143<sup>7</sup></i>	----	----	----	----

**Note 1:** ALLOWABLE loads are shown in the **LARGE BOLD** font, *Ultimate* loads are shown in *smaller italic* font. **Note 2:** Testing conducted in accordance with ICC AC70 & ASTM E1190. **Note 3:** Safety factors are based on coefficient of variation. In accordance with ICC AC70, the safety factor will be no less than 5. **Note 4:** Cyclic, fatigue, shock loads, and other design criteria may require a different safety factor. **Note 5:** Job site testing may be required to determine actual job site values. **Note 6:** Values shown are for fastenings that have the entire pointed end of the fastener driven through the steel plate; except as noted below. **Note 7:** Fastener penetration is 3/8" minimum. **Note 8:** Fastener penetration is 7/16" minimum. **Note 9:** Fastener penetration is 1/2" minimum. **Note 10:** For Sl: 1 lbf = 4.448 N, 1 inch = 25.4 mm, 1 ksi = 6.89MPa

### Fasteners in Lightweight Concrete

PART NUMBER SERIES	SHANK DIAMETER (INCH)	MINIMUM PENETRATION (INCH)	ALLOWABLE WORKING VALUES INSTALLED IN 3000 PSI LIGHTWEIGHT CONCRETE							
			ALLOWABLE LOAD – <i>Ultimate Load</i>							
			3000 PSI LIGHTWEIGHT W/DECKING				3000 PSI LIGHTWEIGHT			
			LOWER FLUTE TENSION	LOWER FLUTE SHEAR	TENSION	SHEAR	TENSION	SHEAR		
1500 SERIES	0.145	3/4	<b>76</b> <i>395</i>	<b>260</b> <i>1409</i>	<b>167</b> <i>837</i>	<b>179</b> <i>894</i>	----	----		
		1	<b>134</b> <i>668</i>	<b>265</b> <i>1505</i>	<b>200</b> <i>998</i>	<b>228</b> <i>1141</i>	----	----		
		1-1/4	<b>157</b> <i>784</i>	<b>269</b> <i>1344</i>	<b>333</b> <i>1664</i>	<b>400</b> <i>2090</i>	----	----		
		1-1/2	<b>233</b> <i>1163</i>	<b>346</b> <i>1728</i>	<b>391</b> <i>1957</i>	<b>410</b> <i>2050</i>	----	----		
SP SERIES	.150/.180	1	<b>119</b> <i>593</i>	<b>336</b> <i>1679</i>	<b>226</b> <i>1129</i>	<b>250</b> <i>1249</i>	----	----		
		1-1/4	<b>175</b> <i>957</i>	<b>372</b> <i>1860</i>	<b>329</b> <i>1644</i>	<b>377</b> <i>1885</i>	----	----		
		1-1/2	<b>179</b> <i>1055</i>	<b>426</b> <i>2128</i>	<b>406</b> <i>2030</i>	<b>380</b> <i>1900</i>	----	----		
9100 SERIES	0.205	3/4	<b>70</b> <i>351</i>	<b>277</b> <i>1386</i>	----	----	----	----		
		1	<b>112</b> <i>559</i>	<b>378</b> <i>1891</i>	----	----	----	----		
		1-1/4	<b>118</b> <i>689</i>	----	----	----	----			

**Note 1:** ALLOWABLE loads are shown in the **LARGE BOLD** font, *Ultimate* loads are shown in *smaller italic* font. **Note 2:** Testing conducted in accordance with ICC AC70 & ASTM E1190. **Note 3:** Safety factors are based on coefficient of variation. In accordance with ICC AC70, the safety factor will be no less than 5. **Note 4:** Values shown in concrete are for the fastener only. Connected members must be investigated separately. **Note 5:** Cyclic, fatigue, shock loads, and other design criteria may require a different safety factor. **Note 6:** Job site testing may be required to determine actual job site values. **Note 7:** For Sl: 1 lbf = 4.448 N, 1 inch = 25.4 mm, 1 ksi = 6.89MPa

## TE POWDER PERFORMANCE/SUBMITTAL

**Ramset fasteners may be specified by their type or catalog number to satisfy fastening requirements.**

### PIN SPECIFICATIONS

Made from AISI 1060-1065 steel. Austempered to a core hardness of 52-56 Rc  
 Typical tensile strength: 270,000 psi  
 Typical shear strength: 162,000 psi

#### Standard Finishes

Mechanical zinc plate to a minimum thickness of .0002 meets requirements of ASTM B695—Class 5 Type 1

### APPROVALS/LISTING

ICC Evaluation Service, Inc.

#ESR-2690 Sill Plate  
 #ESR-1799 Powder Pins & Clips

City of Los Angeles

#RR-22668 Powder pins

### PERFORMANCE TABLES

#### Fasteners in Normal Weight Concrete

PART NUMBER SERIES	SHANK DIAMETER (INCH)	MINIMUM PENETRATION (INCH)	INSTALLED IN SOLID CONCRETE CONCRETE COMPRESSIVE STRENGTH ALLOWABLE LOAD – <i>Ultimate Load</i>											
			2000 PSI				4000 PSI				6000 PSI			
			TENSION (LBS)		SHEAR (LBS)		TENSION (LBS)		SHEAR (LBS)		TENSION (LBS)	SHEAR (LBS)		
TE	0.157	3/4	<b>71</b>	<i>627</i>	<b>116</b>	<i>713</i>	<b>71</b>	<i>559</i>	<b>116</b>	<i>685</i>	<b>109</b>	<i>753</i>	<b>117</b>	<i>712</i>
		1	<b>197</b>	<i>986</i>	<b>216</b>	<i>1463</i>	<b>258</b>	<i>1390</i>	<b>216</b>	<i>1421</i>	<b>214</b>	<i>1313</i>	<b>383</b>	<i>1998</i>
		1-1/4	<b>264</b>	<i>1399</i>	<b>283</b>	<i>1626</i>	<b>377</b>	<i>1886</i>	<b>317</b>	<i>1846</i>	<b>415</b>	<i>2074</i>	<b>349</b>	<i>1858</i>
		1-1/2	<b>212</b>	<i>1453</i>	<b>297</b>	<i>1719</i>	<b>242</b>	<i>1211</i>	<b>479</b>	<i>2393</i>	-----	-----	-----	-----

#### Fasteners in Lightweight Concrete

PART NUMBER SERIES	SHANK DIAMETER (INCH)	EMBED (INCH)	3000 PSI LIGHTWEIGHT CONCRETE			
			TENSION (LBS)		SHEAR (LBS)	
TE SERIES	0.157	3/4	<b>152</b>	<i>1010</i>	<b>159</b>	<i>998</i>
		1	<b>325</b>	<i>1625</i>	<b>347</b>	<i>1737</i>
		1-1/4	<b>358</b>	<i>1790</i>	<b>437</b>	<i>2239</i>
		1-1/2	<b>466</b>	<i>2332</i>	<b>478</b>	<i>2392</i>

**Note 1:** ALLOWABLE loads are shown in the **LARGE BOLD** font, Ultimate loads are shown in smaller italic font. **Note 2:** Testing conducted in accordance with ICC AC70 & ASTM E1190. **Note 3:** Safety factors are based on coefficient of variation. In accordance with ICC AC70, the safety factor will be no less than 5. **Note 4:** Values shown in concrete are for the fastener only. Connected members must be investigated separately. **Note 5:** Cyclic, fatigue, shock loads, and other design criteria may require a different safety factor. **Note 6:** Job site testing may be required to determine actual job site values. **Note 7:** Minimum edge distance is 3 inches unless otherwise approved. **Note 8:** For SI: 1 lbf = 4.448 N, 1 inch = 25.4 mm, 1 ksi = 6.89MPa

## PERFORMANCE TABLES

### Installed in A36 Structural Steel (inches)

PART NUMBER SERIES	SHANK DIA. (INCH)	SHANK TYPE	3/16		1/4		3/8		1/2		≥ 3/4	
			TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR
TE SERIES	0.157	KNURLED	<b>323</b> <i>1739</i>	<b>606</b> <i>3257</i>	<b>562</b> <i>3022</i>	<b>673</b> <i>3621</i>	<b>934</b> <i>5095</i>	<b>820</b> <i>4473</i>	<b>603</b> <i>3286</i>	<b>766</b> <i>4178</i>	<b>343</b> <sup>6</sup>	<b>496</b> <sup>6</sup>

### Installed in A572-GR50 Structural Steel (inches)

PART NUMBER SERIES	SHANK DIA. (INCH)	SHANK TYPE	3/16		1/4		3/8		1/2		≥ 3/4	
			TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR
TE SERIES	0.157	KNURLED	<b>442</b> <i>2400</i>	<b>676</b> <i>3674</i>	<b>630</b> <i>3747</i>	<b>662</b> <i>3942</i>	<b>760</b> <i>4421</i>	<b>725</b> <i>4218</i>	<b>582</b> <sup>5</sup> <i>3188</i>	<b>532</b> <sup>5</sup> <i>2851</i>	<b>311</b> <sup>5</sup>	<b>469</b> <sup>5</sup>

- Notes:**
- 1) Fasteners tested to ASTM E1190 & ICC-ES AC70
  - 2) Allowable loads are shown in bold font, ultimate loads are shown in smaller, italic font
  - 3) Allowable loads and safety factors are based on coefficient of variation in accordance with ICC AC70, the safety factor will be no less than 5
  - 4) Values shown for steel base materials have the pointed end of the fastener driven through the steel plate
  - 5) Fastener penetration into steel must be minimum 7/16 inch
  - 6) Fastener penetration into steel must be minimum 3/8 inch
  - 7) For SI: 1 lbf = 4.448 N, 1 inch = 25.4 mm, 1 ksi = 6.89MPa

### Fasteners Installed Through Metal Deck into Minimum 3,000 PSI Lightweight Concrete

PART NUMBER SERIES	SHANK DIAMETER (INCH)	SHANK DESCRIPTION	MINIMUM PENETRATION (INCH)	3-INCH DEEP W TYPE STEEL DECK		1-1/2 INCH DEEP B TYPE STEEL DECK			
						UPPER FLUTE		LOWER FLUTE	
				TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)	TENSION (LBS)	SHEAR (LBS)
TE	0.157	SMOOTH-TAPERED	3/4	<b>106</b> <i>529</i>	<b>265</b> <i>1326</i>	<b>131</b> <i>656</i>	<b>261</b> <i>1305</i>	<b>154</b> <i>769</i>	<b>307</b> <i>1537</i>
			1	<b>152</b> <i>761</i>	<b>327</b> <i>1634</i>	<b>156</b> <i>782</i>	<b>273</b> <i>1365</i>	<b>138</b> <i>692</i>	<b>265</b> <i>1326</i>
			1-1/4	<b>164</b> <i>821</i>	<b>330</b> <i>1650</i>	-----	-----	-----	-----
			1-1/2	<b>238</b> <i>1191</i>	<b>448</b> <i>2240</i>	-----	-----	-----	-----

- Note 1:** ALLOWABLE loads are shown in the LARGE BOLD font, Ultimate loads are shown in smaller italic font. **Note 2:** Testing conducted in accordance with ICC AC70 & ASTM E1190. **Note 3:** Safety factors are based on coefficient of variation. In accordance with ICC AC70, the safety factor will be no less than 5. **Note 4:** Values shown in concrete are for the fastener only. Connected members must be investigated separately. **Note 5:** Cyclic, fatigue, shock loads, and other design criteria may require a different safety factor. **Note 6:** Job site testing may be required to determine actual job site values. **Note 7:** Minimum edge distance is 3 inches unless otherwise approved. **Note 8:** For SI: 1 lbf = 4.448 N, 1 inch = 25.4 mm, 1 ksi = 6.89MPa

### Fasteners Driven into Concrete Masonry Units (CMU Block)

PART NUMBER SERIES	SHANK DIAMETER (INCH)	EMBED	HOLLOW UNGROUTED CMU				GROUT-FILLED CMU					
			FACE SHELL		MORTAR JOINT		FACE SHELL		MORTAR JOINT		TOP OF GROUTED CELL	
			TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR
TE	0.157	1	<b>33</b> <i>329</i>	<b>100</b> <i>693</i>	<b>42</b> <i>443</i>	<b>68</b> <i>746</i>	<b>139</b> <i>875</i>	<b>145</b> <i>936</i>	<b>91</b> <i>950</i>	<b>127</b> <i>1328</i>	<b>165</b> <i>851</i>	<b>171</b> <i>922</i>

- For SI: 1 Inch = 25.4 mm, 1 lbf = 4.448 N.  
 Fasteners must be installed a minimum of 5.1 inches from the end of the wall.  
 Fasteners must be installed at the center of the CMU cell. No more than one fastener may be installed in an individual CMU cell  
 Applicable to fasteners installed in the horizontal mortar joint (bed joint). Minimum fastener spacing must be 5.1 inches  
 Allowable shear load value applies to load applied perpendicular to the mortar joint  
 Fastener must be installed vertically at the top, center of grouted cell  
 Shear load can be in any direction perpendicular to the axis of the fastener

TE Embedment depth is easily identifiable by head stamps.





## **National Headquarters**

120 Travail Road  
Markham, Ontario, L3S 3J1

Tel: 905-471-7403  
800-387-9692

Fax: 905-471-7208  
800-668-8688

## **Technical and Customer Service Support**

Tel: 800-387-9692

Fax: 800-668-8688

## **Regional Warehouses**

- Markham, Ontario
- Calgary, Alberta

## **Take Advantage of these Contractor Services from ITW Construction Products Canada**

From job sites to engineering firms, from Safety Seminars to on-site services, we hope you take advantage of our many contractor services— at no charge! After all, it's one thing to offer the quality products you need to do your job. It's another to provide you with superior service, engineering expertise and total product support.

At ITW Construction Products Canada, we are proud of the partnerships we have built through the years with our distributor network and contractors. Thanks to quality products, innovative services and on-time delivery, we will continue to build new relationships and strengthen existing ones today... and into the next century.

- Factory representatives with years of training and service experience will go out to your job site to provide you with product, service and technical assistance.
- We provide architects and engineers with complete submittal packages which gives them the technical data needed to specify ITW Construction Products Canada products. Contact your ITW Construction Products Canada Distributor or your nearest Customer Service location to request submittal packages.

### **Technical Application Assistance:**

- Our staff of application specialists are ready to assist you with any type of application or code approval question during any phase of your project. Call 1-800-387-9692 between 8:00 a.m. and 5:00 p.m. EST, Monday through Friday.

### **Distributed By**



The information and recommendations in this document are based on the best information available to us at the time of preparation. We make no other warranty, expressed or implied, as to its correctness or completeness, or as to the results or reliance of this document.

Ramset, T4, T3, Trakfast, GypFast, Mastershot, Triggershot, Hammershot, PowerPoint, TE Pin and Climacoat are trademarks of Illinois Tool Works, Inc.

A7+, C6+, Dynabolt, G5, Hammer-Set, LDT, Multi-Set II, Poly Set, Red Head, Redi-Drive, S7, Striker, and Trubolt are trademarks of ITW Red Head and Illinois Tool Works, Inc.

Teks, TruGrip GT, Scots, Maxiseal, Dek-Cap, Tapcon, SG, Tapcon, Maxi-Set Tapcon, Condrive, E-Z Ancor, E-Z Toggle, Twist-N-Lock, E-Z Lite, E-Z Mini, Stud Solver, Hi-Lo, S-12, Backer-On, Rock-On, Decking, Dec-U-Drive, Dek-Cap, Grid-Mate, Grid-Mate, PB, Climaseal, Spex, Climacoat, UltraShield, Climashield and Building Ideas That Work are trademarks of ITW Buildex and Illinois Tool Works, Inc.

Sammys, Sammy X-Press, Sammy X-Press It, Sammy X-Press Swivel, Sammy X-Press Sidewinder, Tapcon, Sammy Saddle, Speedy Pole Tool, Spot-Rite Level, and Truss-T Hanger are trademarks of ITW Buildex and Illinois Tool Works, Inc.

The term "Paslode" is a trademark and the Paslode logo and all related product and service names, designs and slogans are Paslode trademarks. Paslode, RounDrive, Impulse, Positive Placement are registered trademarks, PowerFramer and quicklode are trademarks of Illinois Tool Works.

R4, RSS, Kameleon, Fin/Trim, RT Composite, Low Profile Cabinet, Pheinox, Top Star, VWS, Caliburn, and The GRK Fasteners Canada Ltd. and all associated designs and logos are trademarks of GRK Fasteners Canada Ltd., used under license.

Hiiti is a registered trademark of Hilti, Corp.

DensGlass is a registered trademark of Georgia Pacific Building Products.

Dekstrip, Dektite, Retrofit Dektite, and Dektite are registered trademarks of Deks Industries Pty Ltd.

Phillips Square-driv is a registered trademark of the Phillips Screw Company.